

AVerEPack300

Digital Slide Presenter

NEW and improved AVerEPack300, digital slide presenter, supports resolution up to 1024 x 768! Forget about bringing your laptop to meetings anymore because the AVerEPack300 allows you to conduct instant slide presentations without the need of a desktop or notebook computer. Simply store all of your slide PowerPoint files or variety of other images into a CompactFlash card* and insert the card into the AVerEPack300. Connect to the PC's USB or parallel printer port, and then copy over the specific files. Once the desired images have been downloaded, disconnect the AVerEPack300 from the computer, and can then connect it to any television, LCD projector or VGA monitor.

*CompactFlash card not included.



Manuf sku: EPACK300

FEATURES:

- Windows® 95/98/2000 compatible
- Connects directly to USB or PC printer port (Windows® 95 does not support USB; Windows® 2000 does not support printer port)
- Supports up to 1024 x 768 VGA output resolution
- Supports SPP (normal)/EPP/ECP/EPP+ECP
- Fully functional remote control
- Supports ppt** (PowerPoint® 2000), jpg, bmp, pcx, & tif file formats
- Changeable presentation countdown timer
- Slide Sequence Editing: cut, copy, paste, delete, hide and reference
- Quick page reference display
- Supports multiple image folder
- Built-in touch button control panel
- 3 Exclusive Patented Presentation Features:
 - AVerMedia Spot
 - AVerMedia Pointer
 - AVerMedia SpyLight
- 4 Zoom Functions:
 - Regular Zoom and Pan
 - AVerMedia Area-Zoom*
 - AVerMedia Pointer-Zoom*
 - AVerMedia Spot-Zoom*
- 16-Slide Preview
- Horizontal/Vertical screen panning
- Horizontal/Vertical picture positioning
- Multiple Level Flicker-Filter selections for Sharpness control (only for TV)
- Up to 4 levels of brightness control
- Supports Composite/S-Video/RGB/VGA output
- TV/VGA output switchable
- NTSC and PAL switchable (does not support PAL-N & PAL-M)

**Slide presentation only

SPECIFICATIONS:

- Input Signal: USB or Printer Port
- Output Signal:
 - TV: Composite/S-Video NTSC and Pal Switchable (does not support PAL-N and PAL-M)
 - VGA: Support Res: (640 x 480, 800 x 600, 1024 x 768)
- Power Supply: 6.0VDC Power Adapter
- Dimensions:
 - Base unit: 6.02" x 4.33" x 1.42"
 - Remote unit: 6.22" x 2.20" x 1"
- Weight:
 - Base unit: 0.55 lb
 - Remote unit: 0.22 lb
- Warranty: 1 year parts & labor
- Compliance: FCC class B

SYSTEM REQUIREMENTS:

- CPU: Pentium® 166 MMX or better recommended
- Memory: 32MB or higher recommended
- OS: Windows 95/98/2000
- Peripheral I/O: USB or Printer Port
- Storage Media: Requires CompactFlash Card up to 32MB (not included)

PACKAGE INCLUDES:

- AVerMedia AVerEPack300 unit
- Remote Control
- S-Video Cable
- AV Cable
- VGA Cable
- USB Cable
- Application Software
- 6 VDC Power Adapter
- 2 Batteries
- Manual

Features subject to change without notice

*Patent-Pending Features